

## Platform

2.50 m X 5.35 m Platform (7.55 m extended)  
Single hydraulic powered deck extension  
Composite treated wooden floor  
Fold-down/drop-down handrails  
Self-closing gate  
Removable platform console box  
Platform console function status LED's<sup>1</sup>  
Lanyard attach points  
Proportional drive control  
Load sensing system  
Two speed drive selection  
Hydraulic differential lock

## Power & Transmission

Deutz D2011L04i (42kW) diesel engine  
Gull wing steel engine / valve compartment hoods  
Engine monitoring system with integral shut-down  
Hydraulic transmission  
Four wheel drive  
Drive disconnect/brake release

<sup>1</sup> Indicator LED lights on platform control console for tilt, high drive, lift, drive and overload interlocks.

## Functional Equipment & Accessories

Nivolux self-levelling hydraulic jacks  
Steel mesh scissor arm guards  
315/80 R22.5 foam filled lug tread tyres  
Oscillating rear axle  
3 degree tilt indicator light with cut-out  
Ground control selector switch with key lock  
Full grease lubrication on all scissor arm bushings  
Scissor maintenance prop  
Manual descent system  
Hour meter  
Horn  
Travel alarm  
Lifting/tie down lugs

## Available Options

AC cable to platform

**JLG Industries Inc.**  
Polaris Avenue 63  
2132 JH Hoofddorp  
The Netherlands  
Tel: +31 (0)23 565 5665  
Fax: +31 (0)23 557 2493  
e-mail address: europe@jlg.com  
**www.jlgeurope.com**  
An Oshkosh Corporation Company

Printed in UK  
FORM No.: DS019-0208-500  
PART NO.: DS019-ENGLISH



## 210-25

A. Platform height - elevated	21.00 m
B. Platform height - lowered	3.00 m
C. Platform railing height	1.10 m
D. Stowed height (rails folded)	3.20 m
E. Platform size	2.50 m x 5.35 m
F. Platform length fully extended	7.55 m
G. Overall width	2.50 m
H. Overall length	5.75 m
I. Wheelbase	3.90 m
Ground clearance	0.26 m
Platform capacity	1,000 kg
Capacity on deck extension	800 kg
Lift/lower time	100 / 75 sec
Maximum drive height	21.00 m
Deck extension	Hydraulic
Machine weight <sup>1</sup>	15,000 kg
Maximum ground bearing pressure	5.0 kg/cm <sup>2</sup>
Drive speed - high	2.3 km/h
Drive speed - elevated	0.5 km/h
Gradeability (4WD)	30%
Turning radius - inside	1.50 m
Turning radius - outside	6.20 m
Axle oscillation	0.15 m (±)
Tyres	315/80 R22.5 Foam Filled
Diesel engine	42 kW Deutz D2011L04i
Fuel tank capacity	90 L
Hydraulic system	325 L

<sup>1</sup>Certain options or country standards may increase weight and/or dimensions.

